# **CONFINED SPACE VENTILATION**

### MANHOLE GUARD RAILS

- Simple one-piece construction offers easy, no-tools assembly
- Rail locks open and two hooking chains provide protected entry and exit
- Rail accommodates signs, flags or lights, and it can be used with guard rail tents, umbrellas or a winch
- Designed to protect an area 33" L x 33" W, this 42" high guard rail collapses to only 44" L x 44" W x 4" H for easy storage
- Strong, one-inch tubular 0.078 gauge steel construction is powder coated in safety yellow for a durable finish and for high visibility
- · Weight: 34 lbs.



Model	Mfg.	Price
No.	No.	/Each
BB195	9401	

## MANHOLE SHIELDS

- · Constructed of rugged polyethylene
- 12" high shield uniquely designed to fit 28", 30" or 32" manholes with an inflatable seal that ensures a positive fit
- Protects against street level water and mud up to 12"
- Shield weighs 50% less than metal shields and will not dent, nick or rust
- Bright yellow body resist fading




**ALLEGRO** 

4	4	L	L	E	(	31	R	C	)
7	N	D	U	s		R		E	s
				$\overline{}$					

Model	Mfg.	Price
No.	No.	/Each
BB202	9401-12	

## MANHOLE LID LIFTERS

- Toughest manhole covers are easy to move with this one-piece lifter
- Features a long all-steel handle that provides the leverage necessary to fit the heaviest manhole lids
- For safe storage, the alloy steel hook recesses and locks into the pole
- Rubber grips on the handle and foot prevent slips, and cadmium plating fights rust
- 42" long, 9 lbs.



Model	Mfg.	Price
No.	No.	/Each
BB204	9401-20	

## TENT HEATERS

- Rugged, heavy-duty design with an all-steel housing, enclosed heating elements and a sealed motor
- Powerful heater raises the temperature by 50 °F (10 °C) in a work tent
- Requires 110 V AC and has an output of 1500 W
- of 5000 BTU with 115 CFM airflow
  Dimensions: 12" x 8" x 12"
- Weight: 14 lbs.





Model	Mfg.	Price
No.	No.	/Each
BB194	9401-50	

### **DELUXE WORK TENTS**

- · Easy to use and very durable
- Feature quick set-up from the inside or outside, with the fibreglass rod frame
- Frames uniquely designed to not pull out or poke through the fabric
- · A handy attached roll-up flap provides compact storage and easy transport
- One-door design with zipper closure, or two-door design with one zipper closure and one roll-up door
- Pitch roof style provides extra headroom, structural strength and repels snow and water
- Frame rods are bolted for increased stability
- and the unbreakable hinges are made of rolled steel
- Free-standing structural stability excellent in windy conditions
   Includes: Blower duct tube in the rear of the tent and a covered window



Model	Mfg.		Dimensions				Price
No.	No.	Doors	W'x	D	<b>'</b> )	C H'	/Each
BB187	9401-66	1	6 x	6 ۲	)	6 1/2	
BB189	9401-88	1	8 x	8 ۲	)	7 1/2	
BB190	9402-66	2	6 x	( 6	)	6 1/2	
BB192	9402-88	2	8 x	8 ۲	)	7 1/2	