


POLYESTER CORD STRAPPING

- Tougher, stronger, and safer than polypropylene strapping
- Will not scratch or mar delicate surfaces
- Available in Uniline bonded cord strapping and crosswoven cord strapping
- Uniline cord is manufactured by bonding fibres together and is easy to tie
- Crosswoven cord strapping has a cross weave added between the fibres
- Crosswoven strapping will not split or fray
- Used only in manual applications
- Polyester cord strapping offers excellent resistance to moisture
- Frequently used in outdoor applications
- Heavy-duty polyester sizes are frequently used in lumber applications, agricultural and boat industries



Bonded



Woven



INDUSTRIAL WIRE BUCKLES

3/4", 1000/box
Model No. PB908
Price/Each \$



DISPENSER

Model No. PB753
Price/Each \$

Model No.		Strap Width"	Strength lbs.	Feet /Coil	Price/Each	
Bonded	Woven				Bonded	Woven
PB017	PB018	1/4	300	7800		
PB019	PB020	3/8	450	5250		
PB021	PB022	1/2	600	3900		
PB023	PB024	5/8	725	3000		
PB025	PB026	3/4	900	2100		

POLYESTER STRAPPING

- Ideal for medium to heavy-duty palletizing
- Moisture-resistant, safe to handle and recyclable
- Approved by the Association of American Railroads (AAR)
- Strap Thickness: 0.035"
- Colour: Green
- Core Size: 16" x 6"



KLETON

Model No.	Grade	Strap Width"	Strength lbs.	Feet /Coil	Wt. lbs.	Price /Each
PG175	Manual	5/8	1400	4000	55.65	

SERRATED STRAPPING SEALS

- Serrated seals for use with polyester strapping



KLETON

Priced per Box

Model No.	Type	Fits Strap Width"	Qty /Box	Price /Each
PF991	Open	5/8	1000	

POLYESTER CORD HANDI-PAK

- Convenient self-dispensing coil for small uses or on job site packaging
- Contains 100 wire buckles

Model No.	Type	Strap Width"	Break Strength lbs.	Feet /Coil	Price /Each
PB027	Bonded	1/2	600	750	
PB028	Woven	1/2	600	750	

CORDEX



POLYPROPYLENE STRAPPING SEALERS

- Heat treated steel construction for superior strength and durability
- Prevents strapping from loosening during transit
- Long 18" handle requires less effort
- Use on open steel seals



KLETON

Model No.	Strap Width"	Strap Thickness"	Price /Each
PA555	1/2	≤ 0.027	
PA556	5/8	0.023 - 0.039	
PF459	3/4	≤ 0.027	

POLYPROPYLENE & POLYESTER STRAPPING TENSIONERS

- Ideal for applications on flat surfaces
- Accepts strapping 3/8 - 3/4" wide and up to 0.035" thick
- Superior design and performance
- Premium copper bushings
- Built-in strapping cutter

KLETON

Model No. PC939
Price/Each \$

