

1/2" DUAL RANGE HAMMER DRILLS W/CARRYING CASE

- 1/2" capacity; 7.5 Amp motor
- Trigger-lock, trigger speed control in two ranges: 0-1350 RPM, 0-22 000 BPM; 0-2500 RPM, 0-40 000 BPM; reversing
- Hammer with rotation or rotation only
- Self-stop brush system
- Includes: Depth gauge, side handle, chuck key and case

Model No. TEA141
Mfg. No. 5378-21
Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 7.5
No Load RPM: 0-1350/0-2500
No Load BPM: 0-20000/0-40000
Chuck Type: Keyed
Tool Weight: 6.0 lbs.



Milwaukee

1/2" VSR HAMMER DRILLS

- Lightweight design for less user fatigue
- Dual mode hammer drill/drill for wood, steel or masonry applications
- Variable speed allows for precise hole placement on work surface
- Includes: 360° side handle, depth rod and chuck key with holder

Model No. TSW576
Mfg. No. DW511
Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 6.7
No Load RPM: 0-2700
No Load BPM: 0-46000
Chuck Type: Keyed
Tool Weight: 4.3 lbs.



DEWALT

1/2" DUAL RANGE HAMMER DRILLS

- Trigger speed control in two ranges: 0-1350 RPM, 0-22 000 BPM, 0-2500 RPM, 0-40 000 BPM, reversing
- A removable side handle assists in setting the depth rod for pre-set hole drilling
- Hammer with rotation or rotation only
- Includes: Depth gauge, side handle and chuck key

Model No. TT928
Mfg. No. 5378-20
Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 7.5
No Load RPM: 0-1350/0-2500
No Load BPM: 0-20000/0-40000
Chuck Type: Keyed
Tool Weight: 6.0 lbs.



Milwaukee

1/2" VSR DUAL RANGE HAMMER DRILLS

- High/low speed for high speed drilling or high torque applications
- Lightweight design for less user fatigue
- 360° side handle with depth rod offers greater control
- Includes: Side handle, chuck key and plastic carrying case

Model No. TD944
Mfg. No. DW505K
Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 7.8
No Load RPM: 0-1100/0-2700
No Load BPM: 0-19000/0-46000
Chuck Type: Keyed
Tool Weight: 4.8 lbs.



DEWALT

1/2" HAMMER DRILLS WITH CARRYING CASE

- Anti-vibration system (AVS): Delivers maximum comfort by minimizing vibration
- 2-mode operation: Hammer drill/drill for maximum versatility in wood, metal, and concrete
- 2-speed gear box: Allows the user to select the correct drilling speed for the material and accessory
- 360° side handle with depth gauge
- Includes: Depth gauge, removable side handle and carrying case

Model No. TLZ439
Mfg. No. 5380-21
Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 9.0
No Load RPM: 0-1500/0-3500
No Load BPM: 0-24000/0-56000
Chuck Type: Keyed
Tool Weight: 7.3 lbs.



Milwaukee

1" D-HANDLE SDS ROTARY HAMMER

- SHOCKS - Active Vibration Control® reduces vibration felt by the user at the handles
- Variable speed trigger allows user to instantly control speed
- Mode selector allows for usage in rotary hammer, rotary only, and chiseling applications
- Reversing feature helps release tool from bind up situations, and assists with removal of fasteners
- 360 degree side handle adjusts easily for preference or use in tight spaces

Model No. TLV939
Mfg. No. D25263K
Price/Each \$

SPECIFICATIONS

Solid Bit Capacity: 5/32" - 5/8"
Amperage: 8.0
No Load RPM: 0-1150
No Load BPM: 0-4300
Impact Energy: 2.1 ft.-lbs.
Tool Weight: 7.0 lbs.



DEWALT